

EZMarquee - 1 Line 40 Characters

1 Line 40 Characters - NEMA 12

The 1 Line 40 Char EZMarquee can hold up to a maximum of 40 characters (2") per line and features 1 line of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 12 extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity.

All 1 Line 40 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

Characteristics:

Character Height:	2"
Characters per Line:	40
Number of Lines:	1
Visibility:	100'

1 Line 40 Characters feature:

- 1 line of 40 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 4 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

See the different communication interface options available in the charts below

1 Line of 2", 40 Characters Per line

Model Number	Interface
EZMR-1L40C	RS232 and RS422/485 only
EZMR-1L40C-E	Ethernet included
EZMR-1L40C-D	DeviceNet included
EZMR-1L40C-P	Profibus included

1 Line of 2", 40 Characters Per line

Model Number	Interface
EZMT-1L40C	RS232 and RS422/485 only
EZMT-1L40C-E	Ethernet included
EZMT-1L40C-D	DeviceNet included
EZMT-1L40C-P	Profibus included

1 Line 40 Characters Dimensions

