

# EZMarquee - 4 Lines 20 Characters

## 4 Lines 20 Characters - NEMA 12

The 4 Line 20 Char EZMarquee can hold up to a maximum of 20 characters (2") per line and features 4 lines of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 12 extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity.

All 4 Line 20 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

### Characteristics:

Character Height:	2" / 4" / 6" / 8"
Characters per Line:	20 / 10 / 6 / 5
Number of Lines:	4 / 2 / 1 / 1
Visibility:	100'/200'/300'/400'

## 4 Lines 20 Characters feature:

- 4 lines of 20 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 4 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

See the different communication interface options available in the charts below



Model Number	Interface
<b>EZMR-4L20C</b>	RS232 and RS422/485 only
<b>EZMR-4L20C-E</b>	Ethernet included
<b>EZMR-4L20C-D</b>	DeviceNet included
<b>EZMR-4L20C-P</b>	Profibus included

Model Number	Interface
<b>EZMT-4L20C</b>	RS232 and RS422/485 only
<b>EZMT-4L20C-E</b>	Ethernet included
<b>EZMT-4L20C-D</b>	DeviceNet included
<b>EZMT-4L20C-P</b>	Profibus included

## 4 Lines 20 Characters

### Dimensions

